

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.11.2015

Version: 7

Revision: 02.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Temp Colour System Lacquer
- **Article number:** TEMPS21
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Dental sealing material
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Micerium spa., Via G. Marconi, 83 - 16036 Avegno (GE), Italy, Tel.: +39-0185-7887870, Fax: +39-0185-7887970
- **Further information obtainable from:** Dr. Eugenio Miceli
- **1.4 Emergency telephone number:**
Poison Control Center San Martino Hospital (Genoa, Italy) Tel.: +39-010-352808 (available 24 h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger

- **Hazard-determining components of labelling:**

methyl methacrylate

2-Propensäure, Reaktionsprodukte mit Dipentaerythritol

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.11.2015

Version: 7

Revision: 02.11.2015

Trade name: Temp Colour System Lacquer

(Contd. of page 1)

- **Labelling of packages where the contents do not exceed 125 ml**
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**
methyl methacrylate
2-Propensäure, Reaktionsprodukte mit Dipentaerythritol
- **Hazard statements**
H317 May cause an allergic skin reaction.
- **Precautionary statements**
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Liquid based on methacryl acid ester.

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-75%
CAS: 1384855-91-7	2-Propensäure, Reaktionsprodukte mit Dipentaerythritol Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-25%
CAS: 75980-60-8 EINECS: 278-355-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 2, H361f	< 2.5%

- **Additional information** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** Immediately remove any clothing soiled by the product.
- **After inhalation** Supply fresh air and to be sure call for a doctor.
- **After skin contact**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
Seek medical treatment.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.11.2015

Version: 7

Revision: 02.11.2015

Trade name: *Temp Colour System Lacquer*

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
 - Carbon dioxide
 - Fire-extinguishing powder
 - Foam
 - Water haze
- **For safety reasons unsuitable extinguishing agents** *Water with full jet.*
- **5.2 Special hazards arising from the substance or mixture**
 - Danger of polymerization.
 - Can form explosive gas-air mixtures.
- **5.3 Advice for firefighters**
- **Protective equipment:** *No special measures required.*
- **Additional information**
 - Cool endangered receptacles with water spray.
 - Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Ensure adequate ventilation
 - Avoid eye and skin contact with the substance.
 - Wear protective equipment. Keep unprotected persons away.
 - Keep away from ignition sources
- **6.2 Environmental precautions:**
 - Prevent seepage into sewage system, workpits and cellars.
 - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - When pumping out, please ensure grounding.
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
 - Close container immediately after use and protect product from light incidence.
 - Storage between 10 °C and 25 °C.
- **Information about storage in one common storage facility:** *Store away from foodstuffs.*
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.11.2015

Version: 7

Revision: 02.11.2015

Trade name: *Temp Colour System Lacquer*

(Contd. of page 3)

· 7.3 *Specific end use(s)* No further relevant information available.

SECTION 8: Exposure controls/personal protection

· *Additional information about design of technical facilities:* No further data; see item 7.· 8.1 *Control parameters*· *Ingredients with limit values that require monitoring at the workplace:***80-62-6 methyl methacrylate**

WEL	Short-term value: 416 mg/m ³ , 100 ppm
	Long-term value: 208 mg/m ³ , 50 ppm

· *Additional information:* The lists valid during the making were used as basis.· 8.2 *Exposure controls*· *Personal protective equipment*· *General protective and hygienic measures*

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· *Respiratory protection:*

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A

· *Protection of hands:* Solvent resistant gloves· *Material of gloves* Butyl rubber, BR· *Penetration time of glove material*

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· *Eye protection:* Safety glasses· *Body protection:* Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 *Information on basic physical and chemical properties*· *General Information*· *Appearance:**Form:* Fluid*Colour:* Colourless· *Odour:* Characteristic· *Odour threshold:* Not determined.· *pH-value:* Not determined.· *Change in condition**Melting point/Melting range:* - 48 °C*Boiling point/Boiling range:* 101 °C· *Flash point:* 10 °C· *Flammability (solid, gaseous)* Not applicable.· *Ignition temperature:* 430 °C· *Decomposition temperature:* Not determined.· *Self-igniting:* Product is not selfigniting.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.11.2015

Version: 7

Revision: 02.11.2015

Trade name: *Temp Colour System Lacquer*

(Contd. of page 4)

· Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
· Explosion limits:	
Lower:	<i>2.1 Vol %</i>
Upper:	<i>12.5 Vol %</i>
· Vapour pressure at 20 °C:	<i>47 hPa</i>
· Density:	<i>Not determined</i>
· Relative density	<i>Not determined.</i>
· Vapour density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with Water:	<i>Slightly soluble</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
dynamic:	<i>Not determined</i>
kinematic:	<i>Not determined</i>
· Solvent content:	
Organic solvents:	<i>0.0 %</i>
· 9.2 Other information	<i>No further relevant information available.</i>

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **10.3 Possibility of hazardous reactions** *Exothermic polymerization*
- **10.4 Conditions to avoid** *No further relevant information available.*
- **10.5 Incompatible materials:**
In presence of radical formers (e. g. peroxides), deoxidizing substances, and/or heavy metal ions, polymerization with heat release is possible.
- **10.6 Hazardous decomposition products:**
At temperatures above 250 °C, depolymerisation and the release of starting monomers can arise

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**
methyl methacrylate LD-50 oral >5000 mg/kg rat (lit.)
LD-50 inhalativ 7093 ppm/4h rat (lit.)
- **Primary irritant effect:**
- **Skin corrosion/irritation** *Irritant to skin and mucous membranes.*
- **Serious eye damage/irritation** *Irritating effect.*
- **Respiratory or skin sensitisation** *Sensitisation possible through skin contact.*
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.
Irritant
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** *Based on available data, the classification criteria are not met.*
- **Carcinogenicity** *Based on available data, the classification criteria are not met.*
- **Reproductive toxicity** *Based on available data, the classification criteria are not met.*

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.11.2015

Version: 7

Revision: 02.11.2015

Trade name: **Temp Colour System Lacquer**

(Contd. of page 5)

- **STOT-single exposure** May cause respiratory irritation
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

- **Aquatic toxicity:** No further relevant information available.
- **Type of test** **Effective concentration** **Method** **Assessment**
 Toxicity to fish: LC-50: >79 mg/l OECD 203
 (MMA) NOEC: 40 mg/l ISO 7346
 Time: 96 h EEC84
 Species:
 Oncorhynchus mykiss

Toxicity to Micro- ECO: 100 mg/l starting inhibition
 Organisms Species: of cell growth
 (MMA) Pseudomonas putida

- **12.2 Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**

Components:

methyl methacrylate Biodegradability: 30,7 %
 Time: 28 d
 Method: OECD 301 C
 Valuation: difficult to decompose

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must be specially treated adhering to official regulations.
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1247

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.11.2015

Version: 7

Revision: 02.11.2015

Trade name: *Temp Colour System Lacquer*

(Contd. of page 6)

· **14.2 UN proper shipping name**
· **ADR** 1247 METHYL METHACRYLATE MONOMER, STABILIZED mixture
· **IMDG, IATA** METHYL METHACRYLATE MONOMER, STABILIZED mixture

· **14.3 Transport hazard class(es)**· **ADR**

· **Class** 3 (F1) Flammable liquids.
· **Label** 3

· **IMDG, IATA**

· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**· **ADR, IMDG, IATA** II· **14.5 Environmental hazards:**· **Marine pollutant:** No· **14.6 Special precautions for user** Warning: Flammable liquids.· **Danger code (Kemler):** 339· **EMS Number:** F-E,S-D· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category** 2· **Tunnel restriction code** D/E· **IMDG**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN1247, METHYL METHACRYLATE MONOMER, STABILIZED mixture, 3, II

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.11.2015

Version: 7

Revision: 02.11.2015

Trade name: *Temp Colour System Lacquer*

(Contd. of page 7)

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **National regulations**

· **Information about limitation of use:**

Employment restrictions concerning pregnant and lactating women must be observed.

· **Technical instructions (air):**

Class	Share in %
NK	50-75

· **Waterhazard class:** *Water hazard class 1 (Self-assessment): slightly hazardous for water.*

· **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

H412 Harmful to aquatic life with long lasting effects.

· **Department issuing MSDS:** *Micerium S.p.a.*

· **Contact:** *Dr. Eugenio Miceli*

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· *** Data compared to the previous version altered.**